

STANDARD SIZING CHART

The following chart explain the standard sizes availables for: OptiForm B2X, FXT, SLX, F2X

However, CGP Europe can make tailored casting for your special sizes. We also make custom cut for you to reduce your scrap and get ready to machine material.

		Standard Stock Sizes (diameter or thickness)											Made to order				
	inch	7	1,5	2	2,5	3	3,5	4	4,5	5	5,5	6	7	8	9	10	12
	mm	25	<i>3</i> 8	51	64	76	89	102	114	127	140	152	178	203	229	254	305
Rods	660 mm			•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sheets	660 mm 610 mm	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Sizes Tolerances: Thickness or Diameter [-0mm; +6mm] Lenght & Width [-5mm; +15mm]

OptiForm ® products are warrantied to meet the specifications noted on this sheet

Color: Surface color may vary due to Rod/Sheet thickness. Changes in surface color do not impact the performance of the material. Color is for material identification

Internal Voids: voids are minuscule air bubbles that occur in the manufacturing process. Each part are inspected in quality control. While it is not possible to entirely eliminates these voids CGP Europe warranties each sheet and rod to have no internal voids larger than 3mm and no more than 2 each 30cm between 1mm and 3mm.

CGP